



Material safety data
sheet
Revised 05/18/04

Section 1

Manufacture Information

Manuf/Dist. name: Danny's Dealer Supplies Inc.
Company Address: 1037 Okeechobee Rd. Unit 1
West Palm Beach Fl. 33401
Company phone: 561-822-9994 Fax 561-655-1522
Emergency phone: 800-535-5053 Infotrac 24 hours Medical information
Trade name: Tire Glaze
Part Number: Dds.408
Chemical name: Not Applicable
Chemical Family: Not Applicable
Formula: Proprietary
Product code: Not Applicable

Hazardous material identification

Product name: Tire Glaze Dds.408
Hazard rating: 0 = Insignificant
1 = Slight
2 = Moderate
3 = High
4 = Extreme
* = Special

Health	1
Fire	2
Reactivity	0
Specific	*

Section 2

Hazardous ingredients

Hazardous ingredients See CFR29 § 1910.1200 (i)-(13)
Chemical name CAS number Percentage PEL-OSHA TLV-ACGIH
Mineral Spirits 8052-41-3 >1 500ppm 100ppm
Carcinogens NTP: not listed OSHA: not listed IARC Monograph: no listed

Section 3

Effects of overexposure First aid procedures

Health effects acute and chronic

Eyes: Can cause severe irritation, redness, tearing, blurred vision.
Skin: Prolonged and repeated contact can cause moderate irritation, de-fatting, dermatitis.
Ingestion: Can cause gastro intestinal irritation, nausea, vomiting and diarrhea.
Inhalation: Can cause mild irritation.
Chronic: Inhalation may increase susceptibility to repertory illness.

Emergency First aid procedures

Eyes: Flush with plenty of water for 15 minutes.
Skin: Immediately flush skin with plenty of running water for 30 minutes.
Remove contaminated clothing and wash before reusing.
Ingestion: Do not induce vomiting. Call physician immediately. Drink copious amounts of water or milk, consult physician.
Inhalation: Breathe fresh air. Administer oxygen if breathing is difficult.
Contact a physician if problem continues.
For emergencies contact Infotrac 800-535-5053

Section 4

Physical data

Appearance Yellow clear liquid

Odor	None
Solubility in water	Insoluble in water
Vapor pressure mm hg	2
Boiling/melting point (F)	>300°F
Vapor density (air=1)	none
Evaporation rate (butyl acetate=1)	24
Percentage volatile by weight (%)	>90.00
Specific gravity (water-1)	>0.780

Section 5 Fire, Explosion and Reactivity hazard data

Flash point °F	108°F T.C.C.
Flammability limits in air (%V)	LEL-1% UEL-
Extinguishing media	Regular foam, water fog, carbon dioxide or dry chemicals.
Special fire fighting procedures	Do not enter confined fire area without full bunker gear, including a positive pressure mode breathing apparatus.
Unusual fire and explosion hazards	See additional comments*
Chemical incompatibility	Avoid contact with strong oxidizing agents such as chlorine, permanganate, etc.
Hazardous decomposition products	Burning may produce oxides, and hydrocarbons.
Hazardous polymerization	Will not occur.
Stability	Stable

Section 6 Spill or leak procedures Waste disposal method

Spill or leak procedures	Eliminate all ignition sources. Absorb with suitable absorbent and shovel into containers.
Waste disposal method	Dispose of according to local, state and federal regulations.

Section 7 Precautions for safe handling and use

Respiratory	An appropriate NIOSH approved hydrocarbon canister or respirator for organic vapor should be worn if needed.
Ventilation	Below TLV(s)
Eye protection	Safety glasses should be worn in all industrial operations.
Handling instructions	Avoid eye contact and prolonged contact with skin. Wear protective gloves. Use adequate ventilation. Wash thoroughly after handling.
Work practices	Eye wash fountain and safety shower should be easily accessible. Provide adequate ventilation.
Hygienic practices	Avoid contact with eyes, skin and clothing. Avoid inhalation of product vapors.

Section 8 Special precautions

Handling precautions	Flammable keep away from heat, sparks and open flames. Do not store under freezing conditions. Protect from physical damage.
Maintenance precautions	Do not store near acids or acidic materials or oxidizers. When working with flammable material electrically ground all equipment.
Other precautions	Containers even those that have been emptied will retain product residue and vapors. Always obey hazard

warnings and dispose of containers according to state or local guidelines.

Additional precautions *Unusual fire- Vapors are heavier than air and may travel along ground and could ignite by heat from pilot lights or other flame and ignition sources.

KEEP OUT OF REACH OF CHILDREN